

6

5

4



3

2

1





D

D



C

C



B

B

A

A

- NOTES:
- MATERIAL AND FINISHES:
HOOD, HOOD COVER AND INSERT: CONDUCTIVE COMPOSITE, UL94V-0, COLOR: BLACK.
JACKSCREWS: STEEL, ZINC PLATE WITH CHROMATE SEAL.
COVER SCREWS: STAINLESS STEEL, PASSIVATED.
 - DETAILED PRODUCT, MECHANICAL AND ELECTRICAL INFORMATION IS AVAILABLE IN THE LATEST D-SUB ACCESSORIES PRODUCT PUBLICATION AT CONNECTPOSITRONIC.COM.

BY	SM	CHK	AP	3RD ANGLE	POSITRONIC BELIEVES THE DATA ON THE DRAWING TO BE RELIABLE. THE USER EMPLOYS SUCH INFORMATION AT HIS OWN DISCRETION AND RISK. POSITRONIC ASSUMES NO RESPONSIBILITY FOR RESULTS OBTAINED OR DAMAGES INCURRED FROM USE OF SUCH INFORMATION IN WHOLE OR IN PART.	 Positronic® CONNECTPOSITRONIC.COM
APR	AB	RELEASED DATE:	2022-05-11			
TOLERANCES				SCALE	D9000Z00	SERIES D
±0.03mm [.001 INCHES] FOR MALE CONTACT MATING DIAMETERS ±0.08mm [.003 INCHES] FOR CONTACT TERMINATION DIAMETERS ±0.13mm [.005 INCHES] FOR ALL OTHER DIAMETERS ±0.38mm [.015 INCHES] FOR ALL OTHER DIMENSIONS ±5° FOR ALL ANGLES DIMENSION ARE IN MILLIMETERS [INCHES]				NTS		
TITLE				D9000Z00		
CREATED ON:		SHEET		REV		
2022-05-11		SHEET 1 OF 1		A		

6

5

4

3

2

1