



**DB25F AND XLRM AND XLRF WIRING CHART**

XLR (CHANNEL)	XLR (DESC.)	CABLE (COLOR)	PIN 2 (RED)	PIN 3 (BLACK)	PIN 1 (BARE)
1	XLRF	BROWN	24	12	25
2	XLRF	RED	10	23	11
3	XLRF	ORANGE	21	9	22
4	XLRF	YELLOW	7	20	8
5	XLRM	GREEN	18	6	19
6	XLRM	BLUE	4	17	5
7	XLRM	PURPLE	15	3	16
8	XLRM	GRAY	1	14	2

- NOTES:
- BREAKOUT CABLE LENGTH: 18 +/- 0.75 INCHES. SEE TABLE FOR COLOR.

2. THIS PRODUCT COMES COILED AND PACKAGED IN BAG.
3. MATERIALS:
- XLR CONNECTORS:
    - HANDLE - ZINC ALLOY, NICKEL PLATED
    - HOUSING AND LATCH - ZINC ALLOY, NICKEL PLATED
    - INSULATOR - THERMOPLASTIC, GREEN
    - SOCKET CONTACTS AND PINS - SPECIAL COPPER ALLOY, SILVER PLATED
  - H.S. TUBING - THERMOPLASTIC
  - DSUB:
    - CABLE CLAMP - COPPER, NICKEL PLATED
    - SHELL - STEEL, TIN PLATED
    - INSULATORS - THERMOPLASTIC
    - SCREW LOCKS - BRASS, NICKEL PLATED

4. THIS PRODUCT IS RoHS COMPLIANT.

**CUSTOMER DRAWING**

REV	ECO NUMBER	DATE	BY	APVD
C	27520	06/08/15	PC	TJK
B	26637	10/4/10	RS	TJK
A	26568	7/20/10	RS	TJK

REVISIONS

UNLESS OTHERWISE SPECIFIED

1. ALL DIMENSIONS IN INCHES [mm]

- TWO PLACE DECIMALS ±0.02 [0.5]

- THREE PLACE DECIMALS ±0.005 [0.13]

**DO NOT SCALE DRAWING**

THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.

SIZE	WIDTH	MULT	LBS/M	TEMPER
FINISH		MATERIAL		
SPEC No.		SPEC No.		
FIRST USED ON		SCALE 1:2		
DATE DRAWN	BY	CHKD	APVD	<b>Switchcraft</b> <sup>®</sup>
7/15/09	JGK	RS	TJK	
NAME		PART No.		REV
DB25F TO 4-XLRM & 4-XLRF, RoHS		DB25FXLRMXMLRF		C

SHEET 1 OF 1