

Electronic Components

See specs for product details.

C0402C110M8HACAUTO	
Manufacturer Part Number:	C0402C110M8HACAUTO
Manufacturer/Brand:	KEMET
Part of Description:	CAP CER 0402 11PF 10V ULTRA STAB
Datasheets:	C0402C110M8HACAUTO.pdf
RoHs Status:	RoHs Lead free / RoHS
Stock Condition:	Compliant New original, 2628 pcs Stock Available.
Ship From:	Hong Kong
Shipment Way:	DHL/Fedex/TNT/UPS/EMS

Specifications Part Number C0402C110M8HACAUTO Manufacturer KEMET Description CAP CER 9082 11PF 10V ULTRA STAB Category Capacitors > Ceranic Capacitors Part Status 628 pcs Stock Voltage - Rated 10V Tolerance 4.20% Thickness (Max) 0.022° (0.55mm) Temperature Coefficient X8R Size / Dimension 0.039° L x 0.020° W (1,00mm x 0.50mm) Series C Series C Package / Case AEC-Q200 Pack	See specs for product details.	
Manufacturer KEMET Description CAP CER 0102 11PF 10V ULTRA STAB Categopy Capacitors > Ceramic Capacitors Part Status 2628 pcs Stock Voltage - Rated 10V Tolerance ±2096 Thickness (Max) 0.022* (0.55mm) Temperature Coefficient XBR Size / Dimension 0.039* L x 0.020* W (1.00mm x 0.50mm) Sertes C Ratings AEC-Q200 Packaging Tape & Reel (TR) Package / Case 0402 (1005 Metric) Operating Temperature -55°C ~ 150°C Mounting Type Surface Mount, MLCC Mounting Type Surface Mount, MLCC Manufacturer Standard Lead Time 18 Weeks Lead Free Status / ROHS Status Lead free / ROHS Compliant Height - Seated (Max) - Features Low ESI, High Temperature Failure Rate - Detailed Description 110°£ ±20% 10V Ceramic Capacitor X8R 0402 (1005	Specifications	
Description CAP CER 0402 11PE 10V ULTRA STAB Category Capacitors > Ceramic Capacitors Part Status 2628 pcs Stock Vottage - Rated 10V Tolerance ±20% Thickness (Max) 0.022" (0.55mm) Temperature Coefficient X8R Size / Dimension 0.039" Lx 0.020" W (1.00mm x 0.50mm) Series C Ratings AEC-Q200 Packaging Tape & Reel (TR) Package / Case 0402 (1005 Metric) Operating Temperature -55°C ~ 150°C Mounting Type Surface Mount, MLCC Mounting Type Surface Mount, MLCC Menufacturer Standard Lead Time 18 Weeks Lead Free Status / RoHS Status Lead Free / RoHS Compliant Height - Seated (Max) - Features Low ESL, High Temperature Faiture Status Low ESL, High Temperature Faiture Status Low ESL, High Temperature Faiture Status (Max) 1.0 ESL, High Temperature Faiture Status (Max) 1.0 ESL, High Temperature Faiture Status (M	Part Number	C0402C110M8HACAUTO
Category Capacitors > Ceranic Capacitors Part Status 528 pcs Stock Voltage - Rated 10V Tolerance ±20% Thickness (Max) 0.022* (0.55mm) Temperature Coefficient X8R Size / Dimension 0.039* L x 0.020* W (1.00mm x 0.50mm) Series C Ratings AEC-Q200 Ratings AEC-Q200 Packaging Tape 8. Reel (TR) Poenating Temperature -55°C × 150°C Mounting Type surface Mount, MLCC Mounting Type 10 (Unlimited) Mounting Type 13 Weeks Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Height - Seated (Max) Low ESL, High Temperature Talure Rate - Datable Description 11pf ±20% 10V Ceramic Capacitor XSR 0402 (1005	Manufacturer	KEMET
Part Status 2628 pcs Stock Voltage - Fated 100 Tolerance ±20% Thickness (Max) 0.022" (0.55mm) Temperature Coefficient X8R Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Series C Ratings AEC-Q200 Packaging Tape & Reel (TR) Packaging Temperature -55°C x 150°C Mounting Type 55°C x 150°C Mounting Type 55°C x 150°C Mounting Type 13 Weeks Lead Spacing 13 Weeks Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Height - Seated (Max) 10w Est, High Temperature Fature Rate 1.0w Est, High Temperature Balture Rate 1.1pf ± 20% 100 Ceramic Capactor X8R 0402 (1005	Description	CAP CER 0402 11PF 10V ULTRA STAB
Voltage - Rated 10V Tolerance ±20% Thickness (Max) 0.022" (0.55mm) Temperature Coefficient X8R Size / Dimension 0.039" t x 0.020" W (1.00mm x 0.50mm) Series C Ratings AEC-Q200 Packaging Tape & Reel (TR) Package / Case 0402 (1005 Metric) Operating Temperature -55°C ~ 150°C Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Manufacturer Standard Lead Time 18 Weeks Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low ESL, High Temperature Detailed Description 119F ±20% 10V Ceramic Capacitor X8R 0402 (1005	Category	Capacitors > Ceramic Capacitors
Tolerance ±20% Trickness (Max) 0.022" (0.55mm) Temperature Coefficient X8R Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Series C Ratings AEC-Q200 Packaging Tape 8 Red (TR) Package / Case 0402 (1005 Metric) Operating Temperature -55°C ~ 150°C Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Manufacturer Standard Lead Time 18 Weeks Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low ESL, High Temperature Detailed Describtion 11pF ±20% 10V Ceramic Capacitor X8R 0402 (1005	Part Status	2628 pcs Stock
Thickness (Max) 0.022" (0.55mm) Temperature Coefficient X9R Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Series C Ratings AEC-Q200 Packaging Tape & Red (TR) Package / Case 0402 (1005 Metric) Operating Temperature -55°C ~ 150°C Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Manufacturer Standard Lead Time 18 Weeks Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low ESL, High Temperature Failure Rate - Betabled Description 11pF ±20% 10V Ceramic Capacitor X8R 0402 (1005	Voltage - Rated	10V
Emperature Coefficient X8R Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Series C Ratings AEC-Q200 Packaging Tape & Reel (TR) Package / Case 0402 (1005 Metric) Operating Temperature -55°C ~ 150°C Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Manufacturer Standard Lead Time 18 Weeks Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low ESL, High Temperature Failure Rate 11FF ±20% 10V Ceramic Capacitor X8R 0402 (1005	Tolerance	±20%
Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Series C Ratings AEC-Q200 Packaging Tape & Reel (TR) Package / Case 0402 (1005 Metric) Operating Temperature -55°C ~ 150°C Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Manufacturer Standard Lead Time 18 Weeks Lead Spacing - Lead Free Status / ROHS Status Lead free / ROHS Compliant Height - Seated (Max) - Features Low ESL, High Temperature Failure Rate - Detailled Description 11pF ± 20% 10V Ceramic Capacitor X8R 0402 (1005	Thickness (Max)	0.022" (0.55mm)
SeriesCRatingsAEC-Q200PackagingTape & Reel (TR)Package / Case0402 (1005 Metric)Operating Temperature-55°C ~ 150°CMounting TypeSurface Mount, MLCCMoisture Sensitivity Level (MSL)1 (Unlimited)Manufacturer Standard Lead Time18 WeeksLead Spacing-Lead Free Status / RoHS StatusLead free / RoHS CompliantHeight - Seated (Max)-FeaturesLow ESL, High TemperatureFallure Rate-Betailed Describtion11pF ±20% 10V Ceramic Capacitor X8R 0402 (1005	Temperature Coefficient	X8R
Ratings AEC-Q200 Packaging Tape & Reel (TR) Package / Case 0402 (1005 Metric) Operating Temperature -55°C ~ 150°C Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Manufacturer Standard Lead Time 18 Weeks Lead Spacing - Lead Free Status / ROHS Status Lead free / ROHS Compliant Height - Seated (Max) - Features Low ESL, High Temperature Failure Rate - Detailed Description 11pF ±20% 10V Ceramic Capacitor X8R 0402 (1005	Size / Dimension	0.039" L x 0.020" W (1.00mm x 0.50mm)
PackagingTape & Reel (TR)Package / Case0402 (1005 Metric)Operating Temperature-55°C ~ 150°CMounting TypeSurface Mount, MLCCMoisture Sensitivity Level (MSL)1 (Unlimited)Manufacturer Standard Lead Time18 WeeksLead Spacing-Lead Free Status / RoHS StatusLead free / RoHS CompliantHeight - Seated (Max)-FeaturesLow ESL, High TemperatureFailure Rate-Detailed Description11pF ±20% 10V Ceramic Capacitor X8R 0402 (1005	Series	С
Package / Case 0402 (1005 Metric) Operating Temperature -55°C ~ 150°C Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Manufacturer Standard Lead Time 18 Weeks Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low ESL, High Temperature Failure Rate - Detailed Description 11pF ±20% 10V Ceramic Capacitor X8R 0402 (1005	Ratings	AEC-Q200
Operating Temperature -55°C ~ 150°C Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Manufacturer Standard Lead Time 18 Weeks Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low ESL, High Temperature Failure Rate - Detailed Description 11pF ±20% 10V Ceramic Capacitor X8R 0402 (1005	Packaging	Tape & Reel (TR)
Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Manufacturer Standard Lead Time 18 Weeks Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low ESL, High Temperature Failure Rate - 11pF ±20% 10V Ceramic Capacitor X8R 0402 (1005	Package / Case	0402 (1005 Metric)
Moisture Sensitivity Level (MSL) 1 (Unlimited) Manufacturer Standard Lead Time 18 Weeks Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low ESL, High Temperature Failure Rate - Detailed Description 11pF ±20% 10V Ceramic Capacitor X8R 0402 (1005	Operating Temperature	-55°C ~ 150°C
Manufacturer Standard Lead Time 18 Weeks Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low ESL, High Temperature Failure Rate - Detailed Description 11pF ±20% 10V Ceramic Capacitor X8R 0402 (1005	Mounting Type	Surface Mount, MLCC
Lead Spacing - Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low ESL, High Temperature Failure Rate - Detailed Description 11pF ±20% 10V Ceramic Capacitor X8R 0402 (1005	Moisture Sensitivity Level (MSL)	1 (Unlimited)
Lead Free Status / RoHS Status Lead free / RoHS Compliant Height - Seated (Max) - Features Low ESL, High Temperature Failure Rate - Detailed Description 11pF ±20% 10V Ceramic Capacitor X8R 0402 (1005	Manufacturer Standard Lead Time	18 Weeks
Height - Seated (Max) - Features Low ESL, High Temperature Failure Rate - Detailed Description 11pF ±20% 10V Ceramic Capacitor X8R 0402 (1005	Lead Spacing	-
Features Low ESL, High Temperature Failure Rate - Detailed Description 11pF ±20% 10V Ceramic Capacitor X8R 0402 (1005	Lead Free Status / RoHS Status	Lead free / RoHS Compliant
Failure Rate - Detailed Description - 11pF ±20% 10V Ceramic Capacitor X8R 0402 (1005	Height - Seated (Max)	-
11pF ±20% 10V Ceramic Capacitor X8R 0402 (1005 Detailed Description	Features	Low ESL, High Temperature
Detailed Description	Failure Rate	-
	Detailed Description	11pF ±20% 10V Ceramic Capacitor X8R 0402 (1005
		11pF

You May Be Also Be interested

In:

Applications



C0402C110M8HAC7867 KEMET CAP CER 0402 11PF 10V ULTRA STAB



C0402C111F4HACAUTO CAP CER 0402 110PF 16V ULTRA

Automotive



C0402C111F3JACAUTO CAP CER 110PF 25V U2J 0402



C0402C110M4HAC7867 KEMET CAP CER 0402 11PF 16V ULTRA STAB



C0402C111F4JAC7867 CAP CER 110PF 16V U2J 0402



C0402C111F4HAC7867 CAP CER 0402 110PF 16V ULTRA



C0402C110M4HACAUTO CAP CER 0402 11PF 16V ULTRA STAB



C0402C110M5HACAUTO KEMET CAP CER 0402 11PF 50V ULTRA STAB

C0402C110M8HACAUTO Related keyword

More

C0402C110M8HACAUTO KEMET C0402C110M8HACAUTO Electronic C0402C110M8HACAUTO Price C0402C110M8HACAUTO New

C0402C110M8HACAUTO Data Sheet C0402C110M8HACAUTO Datasheets C0402C110M8HACAUTO PDF C0402C110M8HACAUTO Manufacturer C0402C110M8HACAUTO Picture

C0402C110M8HACAUTO Components C0402C110M8HACAUTO Distributor C0402C110M8HACAUTO Original C0402C110M8HACAUTO Warranted

C0402C110M8HACAUTO Image C0402C110M8HACAUTO Stock C0402C110M8HACAUTO RFO

KEMET C0402C110M8HACAUTO C0402C110M8HACAUTO Part C0402C110M8HACAUTO Inventory C0402C110M8HACAUTO Order Online