

Specifications	
Part Number	5STP 6.3-R
Manufacturer	Bel
Description	FUSE GLASS 6.3A 250VAC 5X20MM
Category	Circuit Protection > Fuses
Part Status	2679 pcs Stock
Voltage Rating - AC	250V
Size / Dimension	0.217" Dia x 0.827" L (5.50mm x 21.00mm)
Series	5STP
Response Time	Slow
Packaging	Bulk
Package / Case	5mm x 20mm (Axial)
Other Names	0652R6300-13
Operating Temperature	-55°C ~ 125°C
Mounting Type	Through Hole
Moisture Sensitivity Level (MSL)	1 (Unlimited)
Melting I²t	160
Manufacturer Standard Lead Time	14 Weeks
Lead Free Status / RoHS Status	Lead free / RoHS Compliant
Fuse Type	Cartridge, Glass
DC Cold Resistance	0.008 Ohms
Current Rating	6.3A
Color	-
Breaking Capacity @ Rated Voltage	63A
Approvals	CCC, CE, CSA, cURus, IMQ, SEMKO, VDE

In: 5STP 6.3-R Bel Fuse Inc. FUSE GLASS 6.3A 250VAC 5X20MM	5STP 630 Bel FUSE GLASS 630MA 250VAC 5X20MM	5STP 500-R Bel Fuse Inc. FUSE GLASS 500MA 250VAC 5X20MM	5STP 500-R Bel FUSE GLASS 500MA 250VAC 5X20MM
5STP 63 Bel FUSE GLASS 63MA 250VAC 5X20MM	5STP 63-R Bel Fuse Inc. FUSE GLASS 63MA 250VAC 5X20MM	5STP 6.3 Bel FUSE GLASS 6.3A 250VAC 5X20MM	5STP 63 Bel Fuse Inc. FUSE GLASS 63MA 250VAC 5X20MM

More

Contact us: **Info@YIC-Electronics.com**
ADD: Unit A5-B5 No.509, 5/F Sing Win Factory Building, 15-17 Shing yip St, Kwun Tong, Kowloon, HongKong.
Copyright © 2023 YIC-Electronics.com - YIC International Co., Limited