

Specifications	
Part Number	FEMTOSMDC020F-2
Manufacturer	Hamlin / Littelfuse
Description	POLYSWITCH .200A RESET FUSE SMD
Category	Circuit Protection > PTC Resettable Fuses
Part Status	95409 pcs Stock
Voltage - Max	9V
Type	Polymeric
Time to Trip	100ms
Thickness (Max)	0.030" (0.75mm)
Size / Dimension	0.063" L x 0.031" W (1.60mm x 0.80mm)
Series	PolySwitch®, femtoSMDC
Resistance - Post Trip (R1) (Max)	3 Ohm
Resistance - Initial (Ri) (Min)	700 mOhm
Resistance - 25°C (Typ)	-
Ratings	-
Packaging	Tape & Reel (TR)
Package / Case	0603 (1608 Metric), Concave
Operating Temperature	-
Mounting Type	Surface Mount
Lead Spacing	-
Height - Seated (Max)	-
Current - Trip (It)	450mA
Current - Max	40A
Current - Hold (Ih) (Max)	200mA
Approvals	CSA, TUV, UL

In: FEMTOSMDC016F-02 Littelfuse Inc. POLYSWITCH .16A RESET FUSE SMD	FEMTOSMDC035F-02 Littelfuse Inc. POLYSWITCH RESET FUSE 0.35A SMD	FEMTOSMDC016F-2 Littelfuse Inc. POLYSWITCH .160A RESET FUSE SMD	FEMTOSMDC010F/15-2 Littelfuse Inc. POLYSWITCH .100A 15V RESET SMD
FEMTOSMDC010F-2 Littelfuse Inc. POLYSWITCH .1A RESET FUSE SMD	FEMTOSMDC035F-2 Littelfuse Inc. POLYSWITCH .350A RESET FUSE SMD	FEMTOSMDC010F-02 Littelfuse Inc. POLYSWITCH RESET FUSE 0.10A SMD	FEMTOSMDC012F-2 Littelfuse Inc. POLYSWITCH .120A RESET FUSE SMD

FEMTOSMDC020F-2 Hamlin / Littelfuse	FEMTOSMDC020F-2 Data Sheet	FEMTOSMDC020F-2 Datasheets	FEMTOSMDC020F-2 PDF	Hamlin / Littelfuse FEMTOSMDC020F-2
FEMTOSMDC020F-2 Electronic	FEMTOSMDC020F-2 Components	FEMTOSMDC020F-2 Distributor	FEMTOSMDC020F-2 Image	FEMTOSMDC020F-2 Part
FEMTOSMDC020F-2 Price	FEMTOSMDC020F-2 Manufacturer	FEMTOSMDC020F-2 Picture	FEMTOSMDC020F-2 Stock	FEMTOSMDC020F-2 Inventory
FEMTOSMDC020F-2 New	FEMTOSMDC020F-2 Original	FEMTOSMDC020F-2 Warranted	FEMTOSMDC020F-2 RFQ	FEMTOSMDC020F-2 Order Online