



Specifications	
Part Number	FEMTOSMDC012F-2
Manufacturer	Hamlin / Littelfuse
Description	POLYSWITCH .120A RESET FUSE SMD
Category	Circuit Protection > PTC Resettable Fuses
Part Status	30445 pcs Stock
Voltage - Max	9V
Type	Polymeric
Time to Trip	100ms
Thickness (Max)	0.030" (0.75mm)
Size / Dimension	0.063" L x 0.031" W (1.60mm x 0.80mm)
Series	PolySwitch®, femtoSMDC
Resistance - Post Trip (R1) (Max)	5.8 Ohm
Resistance - Initial (Ri) (Min)	1.1 Ohm
Resistance - 25°C (Typ)	-
Ratings	-
Packaging	Tape & Reel (TR)
Package / Case	0603 (1608 Metric), Concave
Operating Temperature	-
Mounting Type	Surface Mount
Lead Spacing	-
Height - Seated (Max)	-
Current - Trip (It)	300mA
Current - Max	40A
Current - Hold (Ih) (Max)	120mA
Approvals	CSA, UL

In:


FEMTOSMDC010F/15-2
Littelfuse Inc.
POLYSWITCH .100A 15V RESET
SMD




FEMTOSMDC010F-2
Littelfuse Inc.
POLYSWITCH .1A RESET FUSE
SMD



FEMTOSMDC035F-02
Littelfuse Inc.
POLYSWITCH RESET FUSE 0.35A
SMD



FEMTOSMDC016F-2
Littelfuse Inc.
POLYSWITCH .160A RESET FUSE
SMD



Not Actual Photo
YIC International Co., Limited.

femtoSMDC008F/PSR-28741-02
TE
TE SMD

More

Contact us: **Info@YIC-Electronics.com**
ADD: Unit A5-B5 No.509, 5/F Sing Win Factory Building, 15-17 Shing yip St, Kwun Tong, Kowloon, HongKong.
Copyright © 2023 YIC-Electronics.com - YIC International Co., Limited