

Specifications	
Part Number	TLP590B(C,F)
Manufacturer	Toshiba Semiconductor and Storage
Description	OPTOISOLATOR 2.5KV PHVOLT 6-DIP
Category	Isolators > Optoisolators - Transistor, Photovoltaic
Part Status	2684 pcs Stock
Voltage - Output (Max)	7V
Voltage - Isolation	2500Vrms
Voltage - Forward (Vf) (Typ)	1.4V
Vce Saturation (Max)	-
Turn On / Turn Off Time (Typ)	200μs, 1ms
Supplier Device Package	6-DIP, 5 Lead
Series	-
Rise / Fall Time (Typ)	-
Packaging	Tube
Package / Case	6-DIP (0.300", 7.62mm), 5 Leads
Output Type	Photovoltaic
Other Names	Q3885930
Operating Temperature	-55°C ~ 125°C
Number of Channels	1
Mounting Type	Through Hole
Moisture Sensitivity Level (MSL)	1 (Unlimited)
Lead Free Status / RoHS Status	Lead free / RoHS Compliant
Input Type	DC
Detailed Description	Optoisolator Photovoltaic Output 2500Vrms 1 Channel 6-
Current Transfer Ratio (Min)	-
Current Transfer Ratio (Max)	-
Current - Output / Channel	12μA
Current - DC Forward (If) (Max)	50mA

In:			
TLP590A TOSHIBA TOSHIBA SOP5	TLP591B(C,F) Toshiba Semiconductor and Storage OPTOISOLATOR 2.5KV PHVOLT 6-DIP	TLP592A TOSHIBA TOSHIBA SOP6	TLP591B TOSHIBA TOSHIBA DIP5
TLP590B TOSHIBA TOSHIBA DIP6	TLP590 TOSHIBA TOSHIBA DIP5	TLP591 TOSHIBA TOSHIBA DIP5	TLP590B(C,F) TOSHIBA TOSHIBA DIP5

More

Contact us: **Info@YIC-Electronics.com**
ADD: Unit A5-B5 No.509, 5/F Sing Win Factory Building, 15-17 Shing yip St, Kwun Tong, Kowloon, HongKong.
Copyright © 2023 YIC-Electronics.com - YIC International Co., Limited