

Specifications	
Part Number	FEMTOSMDC010F-02
Manufacturer	Hamlin / Littelfuse
Description	POLYSWITCH RESET FUSE 0.10A SMD
Category	Circuit Protection > PTC Resettable Fuses
Part Status	2633 pcs Stock
Voltage - Max	12V
Type	Polymeric
Time to Trip	100ms
Thickness (Max)	0.033" (0.85mm)
Size / Dimension	0.063" L x 0.031" W (1.60mm x 0.80mm)
Series	PolySwitch®, femtoSMD
Resistance - Post Trip (R1) (Max)	8 Ohm
Resistance - Initial (Ri) (Min)	1.7 Ohm
Resistance - 25°C (Typ)	-
Ratings	-
Packaging	Tape & Reel (TR)
Package / Case	0603 (1608 Metric), Concave
Operating Temperature	-40°C ~ 85°C
Mounting Type	Surface Mount
Lead Spacing	-
Height - Seated (Max)	-
Current - Trip (It)	250mA
Current - Max	40A
Current - Hold (Ih) (Max)	100mA
Approvals	CSA, TUV, UL

In: FEMTOSMDC008F-2 Littelfuse Inc. POLYSWITCH .08A RESET FUSE SMD	FEMTOSMDC012F-2 Littelfuse Inc. POLYSWITCH .120A RESET FUSE SMD	FEMTOSMDC010F/15-2 Littelfuse Inc. POLYSWITCH .100A 15V RESET SMD	FEMTOASMDC010F/15-2 Hamlin / Littelfuse PTC RESET FUSE 15V 100MA 0603
FEMTOSMDC008F-02 Littelfuse Inc. POLYSWITCH RESET FUSE 0.08A SMD	FEMTOSMDC016F-02 Littelfuse Inc. POLYSWITCH .16A RESET FUSE SMD	FEMTOSMDC010F-2 Littelfuse Inc. POLYSWITCH .1A RESET FUSE SMD	FEMTOSMDC005F-2 Littelfuse Inc. POLYSWITCH .05A RESET FUSE SMD

FEMTOSMDC010F-02 Hamlin / Littelfuse	FEMTOSMDC010F-02 Data Sheet	FEMTOSMDC010F-02 Datasheets	FEMTOSMDC010F-02 PDF	Hamlin / Littelfuse FEMTOSMDC010F-02
FEMTOSMDC010F-02 Electronic	FEMTOSMDC010F-02 Components	FEMTOSMDC010F-02 Distributor	FEMTOSMDC010F-02 Image	FEMTOSMDC010F-02 Part
FEMTOSMDC010F-02 Price	FEMTOSMDC010F-02 Manufacturer	FEMTOSMDC010F-02 Picture	FEMTOSMDC010F-02 Stock	FEMTOSMDC010F-02 Inventory
FEMTOSMDC010F-02 New	FEMTOSMDC010F-02 Original	FEMTOSMDC010F-02 Warranted	FEMTOSMDC010F-02 RFQ	FEMTOSMDC010F-02 Order Online